

PRIMAX®



DESCRIPTIVE

- Mechnic Governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for wiring temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1.

Overload is not allowed.

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Intlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

ASSOCIATED UNCERTAINTLY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

PR44LS

Engine make	Perkins
Engine Model	1103A-33TG1
Alternator type	Leroy Somer
Alternator Model	LL1514P

GENERAL CHARACTERISTICS

Frequency (Hz)	50
Reference voltage (V)	400/230
Max power ESP (kVA)	48
Max power ESP (kWe)	42
Max power PRP (kVA)	45
Max power PRP (kWe)	40
Intensity (A)	65
Standard Control Panel	610
Optional control panel DSE	4520

DIMENSIONS AND NOISE LEVELS

DIMENSIONS COMPACT VERSION

Length (mm)	1660
Width (mm)	750
Height (mm)	1250
Dry weight (kg)	750
Tank capacity (L)	150



POWERS

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
415/240	42	48	38	45	60
400/230	40	48	38	45	58
380/220	42	48	38	45	58
240 TRI	40	46	38	45	58
230 TRI	40	45	38	45	58
220 TRI	40	45	38	45	58
220/127	40	45	38	45	58

GENERAL ENGINE DATAS

Engine model	Perkins 1103A-33TG1 3 cylinder
Cylinder arrangement	L
Displacement (C.I.)	3.3
Bore (mm) x Stroke (mm)	105 x 127
Compression ratio	17 : 1
Speed (RPM)	1500
Pistons speed (m/s)	6.35
Maximum stand-by power at rated RPM (kW)	45
Frequency regulation (%)	+/- 2.5%
BMEP (bar)	13.38
Governor type	Mechanical

COOLING SYSTEM

Radiator & Engine capacity (L)	10.2
Max water temperature (°C)	105
Outlet water temperature (°C)	93
Fan power (kW)	1.5
Fan air flow w/o restriction (m ³ /m)	86.5
Available restriction on air flow (mm EC)	20
Type of coolant	cool
Thermostat (°C)	82-94

EMISSIONS

Emission PM (mg/Nm ³)	60
Emission CO (mg/Nm ³)	190
Emission HCNOx (g/kWh)	N/A
Emission HC (mg/Nm ³)	34

EXHAUST

Exhaust gas temperature (°C)	430
Exhaust gas flow (L/s)m ³ /min	15.2
Max. exhaust back pressure (kpa)	10

FUEL

Consumption @ 110% load (L/h)	11.7
Consumption @ 100% load (L/h)	10.5
Consumption @ 75% load (L/h)	7.5
Consumption @ 50% load (L/h)	5.6
Maximum fuel pump flow (L/h)	55

OIL

Oil capacity (L)	7
Min. oil pressure (bar)	1.5
Max. oil pressure (bar)	5
Oil consumption 100% load (L/h)	0.02
Carter oil capacity (L)	6.5

HEAT BALANCE

Heat rejection to exhaust (kW)	45
Radiated heat to ambient (kW)	5
Heat rejection to coolant (kW)	23

AIR INTAKE

Max. intake restriction (mm EC)	625
Intake air flow (L/s)	93

GENERAL DATAS

Alternator brand	Leroy Somer
Alternator type	LL1514P
Number of phase	3
Power factor (Cos Phi)	0.8
Altitude (m)	1000
Overspeed (rpm)	2250
Number of pole	4
Excitation system	Brushless
Insulation class / T° class, continuous 40°C	H / H / 125°K
Regulation	DSR
Harmonic factor, no load TGH/THC	N/A
Wave form : NEMA=TIF-(TGH/THC)	N/A
Wave form : CEI=FHT-(TGH/THC)	N/A
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (%)	+/- 1.5%
Recovery time (Delta U = 20% transient) (ms)	N/A

OTHER DATAS

Continuous Nominal Rating 40°C (kVA)	48
Standby Rating 27°C (kVA)	45
Efficiencies 4/4 load (%)	100
Air flow (m3/s)	0.32
Short circuit ratio (Kcc)	0.50
Direct axis synchro reactance unsaturated (Xd) (%)	325
Quadra axis synchro reactance unsaturated (Xq) (%)	170.5
Open circuit time constant (T'do) (ms)	1500
Direct axis transient reactance saturated (X'd) (%)	22.3
Short circuit transient time constant (T'd) (ms)	41.92
Direct axis subtransient reactance saturated (X"d) (%)	7.4
Subtransient time constant (T"d) (ms)	5.75
Quadra axis subtransient reactance saturated (X"q) (%)	29.5
Zero sequence reactance unsaturated (Xo) (%)	3.6
Negative sequence reactance saturated (X2) (%)	19.2
Armature time constant (Ta) (ms)	1.54
No load excitation current (io) (A)	0.5
Full load excitation current (ic) (A)	2.3
Full load excitation voltage (uc) (V)	N/A
Recovery time (Delta U = 20% transient) (ms)	N/A
Engine start (Delta U = 20% perm. or 50% trans.) (kVA)	N/A
Transient dip (4/4 load) - PF : 0,8 AR (%)	N/A
No load losses (W)	N/A
Heat rejection (W)	6317

HARSEN 620, comprehensive and simple



The 620 is a versatile control unit allowing operation in manual or automatic mode. Equipped with an LCD screen, the user-friendly 620 offers high-quality basic functions to guarantee simple, reliable operation of your generating set.

Offers the following functions:

Standard electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, engine speed, battery voltage, fuel level.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed (> 60 kVA), charging alternator fault, low fuel level, emergency stop.

For more information, please refer to the sales documentation.

DEEP SEA 4520, ergonomic and user-friendly



The highly versatile DSE 4520 control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The 4520 offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

Ergonomics: wheel for navigating around the various menus.

Communication: remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.